



Lathe machine 250x550 mm with inverter and AC motor

Description

Metal lathe, LTC DR 550i is equipped with a speed display and stepless speed, Inverter and AC motor (much more powerful than DC motor, and less susceptible to interference). With induction hardened and ground prism bed. CE equipped.

Metal lathe comes standard with:

Three jaw 125mm

Four jaws 125mm

Chip tray and rear shield

Long feed

Cross feed

4-turn chisel holder

Fixed and movable goggles

LED lighting

Separate emergency stop

Accessory box with change wheels, fixed centers, oil sprayer etc.

RAL 5018 & RAL 7004

Optional:

Chassis

Quick change tool holder

Extra information

Item number	15432	
Model	LTC DR 550I Vario-2	
EAN	8718242560092	
CBS Statistics number	84581900	
Article group	HUVEMA Webshop Machines & Equipment	
Brand	Huvema	
Features	Swing over bed	250 mm
	Distance between centres	550 mm
	Hole through spindle	26 mm
	Engine power	1,5 kW
	Digital readout	No
	Tail stock taper	MT2
	Tailstock spindle travel	80 mm
	Threading metric	0,2-3,5 mm
	Threading whitworth	8-56 TPI
	Swing over cross slide	150 mm
	Cross travel support	135 mm
	Speed range	30-2200 rpm
	Top slide travel	80 mm
	Longitudinal feed	0,06-0,32 mm/rev
	Voltage	230 V
	Machine dimensions	115 x 65 x 50 cm
	Weight	145 kg
	Taper of main spindle	MT4
Packaging dimensions	125 x 63 x 61 cm	

Product images

