



Lathe machine 360x750 mm

Description

With the TOPLINE range of lathes, Huvema offers top quality lathes for every workshop. No matter whether you want to turn regularly, particularly value high precision turning without any hassle or simply value quality: TOPLINE lathes offer all this and more!

In the manufacture of TOPLINE lathes, MEEHANITE is used, a special cast iron alloy that offers significantly better rigidity than traditional cast iron. This MEEHANITE alloy provides wear resistance, lasting accuracy and very high stability. The beds are inductively hardened and ground.

The TOPLINE lathe's cross spindle runs through a bath of oil, which pays off in a longer lifespan. The bronze nuts are made of phosphor bronze, which makes them last a long time.

The lathes in the TOPLINE range are equipped with SKF bearings 3 times. This results in extremely high precision, a long lifespan, a very high stability and a large load capacity. In short: precise work is a permanent standard with these TOPLINE machines.

Standard equipment included with TOPLINE lathes:

- Self-centering 3-jaw chuck
- Stationary steady
- Travelling steady
- 4-way holder for turning chisels
- Worklight
- Protective covers
- Cooling
- Variable speed

Optional for the TOPLINE lathe:

- Digital display
- Independent 4-jaw chuck or other chucks
- Live centre
- Turning tools
- Drill head

TOPLINE lathes are available in various sizes and power ranges.

If you can't find a suitable machine in our standard (stock) range? Please do not hesitate to contact us! Our specialists will be happy to help you find the most suitable machine for your application.

Extra information

| | | |
|-----------------------|---------------------------|---------------------------|
| Item number | 30619 | |
| Model | HU 360x750-4 Topline | |
| EAN | 8718242557573 | |
| CBS Statistics number | 84581900 | |
| Article group | HUVEMA Machinery Industry | |
| Brand | Huvema | |
| Features | Swing over bed | 356 mm |
| | Distance between centres | 750 mm |
| | Hole through spindle | 38 mm |
| | Engine power | 2,2 kW |
| | Swing over cross slide | 220 mm |
| | Center height | 178 mm |
| | Swing in gap | 515 mm |
| | Width of bed | 206 mm |
| | Number of revs | 8 |
| | Speed range | 90-1800 rpm |
| | Spindle nose | D1-4 (DIN 55029, Camlock) |
| | Taper of main spindle | MK 5 |
| | Movement tail stock taper | 110 mm |
| | Tail stock taper | MT 3 |
| | Diameter tail stock taper | 45 mm |
| | Cross travel support | 167 mm |
| | Top slide travel | 100 mm |
| | Threading metric | 0.2 - 7 mm |
| | Threading inch | 4 - 72 TPI |
| | Diameter pitch | 8 - 44 DP |
| | Module pitch | 0.3 - 3.5 MOD |
| | Longitudinal feed | 0.037 - 0.5 mm |
| Cross feed range | 0.018 - 0.25 mm | |
| Voltage | 400 V | |
| Weight | 700 kg | |
| Packaging dimensions | 1700 x 760 x 1550 mm | |
| Article group code | 684672 | |

Product images



