



Lathe 470x2000 mm with variable speed

Description

Precision lathe with hardened and ground bed rails. The oil pump, which can be operated both automatically and manually, ensures that the bed tracks and chisel support remain well oiled. You can choose which parts need to be lubricated. Starting handle with safety device. Emergency stop by foot brake.

Properties:

- precision ground, hardened gears
- overload protection on carriage
- adjusting screws
- service kit and toolbox
- rear panel
- cooling system
- longitudinal feeds

Extra information

Item number	30627
Model	HU 480x2200 VAC Topline
EAN	8718242079150
CBS Statistics number	84589900
Article group	K1 - Machines Industry
Brand	Huvema

	Distance between centres	2000 mm
	Swing over bed	470 mm
	Swing over cross slide	280 mm
	Cross travel support	245 mm
	Swing in gap	690 mm
	Hole through spindle	80 mm
	Threading metric	P 0,5 - P 7 mm
	Tailstock diameter	68 mm
	Tailstock spindle travel	150 mm
	Center height	235 mm
	Width of bed	300 mm
	Longitudinal feed	0,05 - 0,82 mm
Features	Tail stock taper	MT4
	Threading inch	4 - 56 TPI
	Leadscrew diameter	35 mm
	Dimensions l x b x h	3420 x 810 x 1250 mm
	Cross feed range	0,02 - 0,4 mm
	Taper of main spindle	MT7, CAMLOCK D1-8 (DIN 55029)
	Power of main engine	7,5 kW
	Spindle speed values	40 - 2000 rpm
	Coolant pump	0,1 kW
	Voltage	400 V
	Weight	2440 kg
	Spindle nose	D1-11 (DIN 55029, Camlock)

Article group code

684689

Product images



